

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	6MAY2020	RG	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
 RATED VOLTAGE: 500 V AC.
 RATED CURRENT: 13 A Max.
 INSULATION RESISTANCE: 500MΩ Min.
 WITHSTANDING VOLTAGE: 2 KV AC 1 MINUTE.
 FLAMMABILITY: UL94V-0.
 MATING CYCLES: 500 CYCLES.
 CONTACT TYPE: CRIMP CONTACT.
 WIRE RANGE: 0.14-1.0mm² (26-18 AWG)
- CONTACT NEED TO BE ORDERED SEPARATELY.
- CABLE DIAMETER \varnothing 9mm- \varnothing 13.2mm.
- UL CERTIFICATED.

注释:

- 技术参数:
 额定电压: 500V AC.
 额定电流: 13A Max.
 绝缘电阻: 500MΩ Min.
 耐电压: 2 KV AC 1分钟.
 阻燃等级: UL94V-0.
 插拔次数: 500次.
 接线类型: 冷压接.
 接线范围: 0.14-1.0mm² (26-18 AWG)
- 端子需要单独订购.
- 线缆直径 \varnothing 9mm- \varnothing 13.2mm.
- UL认证.

5	CABLE SEALING KIT	SYNTHETIC RUBBER
4	CLAMPING SCREW	ZINC ALLOY
3	INSERT	POLYMER
2	HOOD KIT	ZINC ALLOY
1	SHELL	ZINC ALLOY
ITEM	DESCRIPTION	MATERIAL

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
	ANGLES ±-
MATERIAL	FINISH
-	-
-	-

DWN	6MAY2020
Robert Gan	
CHK	6MAY2020
Gino Yao	
APVD	6MAY2020
Chris Wang	
PRODUCT SPEC	108-137506
APPLICATION SPEC	114-137506
WEIGHT	-
CUSTOMER DRAWING	

PART NUMBER 2374418-1

TE Connectivity

NAME			
N GEN ECONECT 20-29 PLUG CABLE KIT			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	©-2374418	-
SCALE		SHEET	REV
1:1		1 OF 1	A

1470-19 (3/13)