


Jun.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



- NOTES
- ① ACROSS FLATS OF HEXAGON SOCKET OF REF. NO. ⑭ : 1.27.
THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑭ : 0.3 TO 0.4N · m.
 - ② THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑨ AND NO. ⑬ : 2N · m.
 - ③ LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. ⑬ AND NO. ⑭ FROM LOOSENING.
 - 4 ROTATION EXAMPLES OF REF. NO. ① , ⑨ AND ⑬ ARE SHOWN.
 - 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE. PLEASE CONFIRM BEFORE THE USE.

8	PHOSPHOR BRONZE	NICKEL PLATING			
7	STEEL	NICKEL PLATING	15	ACRYLONITRILE BUTADIENE RUBBER	(BLACK)
6	BRASS	NICKEL PLATING	14	STEEL	NICKEL PLATING M2. 6×0.45
5	SILICONE RUBBER	(BLACK)	13	BRASS	NICKEL PLATING
4	BERYLLIUM COPPER	SILVER PLATING 2µm min	12	BRASS	NICKEL PLATING
3	BERYLLIUM COPPER	SILVER PLATING 2µm min	11	SILICONE RUBBER	(BLACK)
2	POLYBUTYLENE TEREPHTHALATE	(BLACK) UL94V-0	10	SILICONE RUBBER	(BLACK)
1	ZINC ALLOY	NICKEL PLATING	9	BRASS	NICKEL PLATING
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.				APPROVED : SU. OBARA 10.10.15 CHECKED : HY. KISHI 10.10.14 DESIGNED : WR. AJIRO 10.10.14 DRAWN : WR. AJIRO 10.10.14	DRAWING NO. EDC3-044335-73 PART NO. HR22-12WTPA-20S(73) CODE NO. CL122-0015-3-73		